

ACCORDING TO THE WORK, HEALTH AND SAFETY REGULATIONS

SECTION 1: IDENTIFICATION

Product identifier

Product Name

GMS Marking fluid.

Other means of identification

Not applicable.

Recommended use of the chemical and restrictions on use

Identified uses Uses advised against For the electrolytic chemical etching of metals Not recommended for use on titanium, plastics, or aluminium substrates. Not for private (household) purposes.

Details of manufacturer or importer

Manufacturer/supplier Address of manufacturer Telephone E-mail

Emergency phone number

Details of the Australian importer are required here <INSERT DETAILS OF AUSTRALIAN IMPORTER> <INSERT DETAILS OF AUSTRALIAN IMPORTER> <INSERT DETAILS OF AUSTRALIAN IMPORTER>

<State an Australian business telephone number from which information about the chemical can be obtained in an emergency>

The emergency information available through this service should be available outside working hours.

SECTION 2: HAZARD(S) IDENTIFICATION

Classification of the hazardous chemical

Classification according to WHS regulations and GHS Version 7

Flammable liquid – Category 2 Acute toxicity - oral - Category 4 Sensitisation – Skin – Category 1A Serious eye damage/irritation – Category 2 Specific target organ toxicity (single exposure) – Category 3 Germ cell mutagenicity - Category 1B Carcinogenicity - Category 1B Toxic to reproduction – Category 2 Specific target organ toxicity (repeated exposure) - Category 2 Aquatic toxicity - chronic - category 3

Label elements, including precautionary statements

According to according to WHS regulations and GHS 7

Hazard symbols





Health hazard



Hazard statementsH225: Highly flammable liquid and vapourH302: Harmful if swallowedH317: May cause an allergic skin reactionH319: Causes serious eve irritation	
H335: May cause respiratory irritation H340: May cause genetic defects H350: May cause cancer H361: Suspected of damaging fertility or the unborn child (oral) (developmental toxicity) H373: May cause damage to organs (respiratory track) through prolon or repeated exposure (inhalation) H412: Harmful to aquatic life with long lasting effects	nged
Precautionary statements P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces—No smoking. P240 Ground/Bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breather fumes/mist/vapours/spray. P264 Wash hands thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/ eye protection/face protection. P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor/physicia you feel unwell. P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in position comfortable for breathing. P338 + P313 IF kin irritation or rash occurs: Get medical advice/attention. P303 + P313 IF SKIN I(or hair): Remove/Take off immediately contaminated clothing. Rinse skin with water/shower. P305 + P351 H P353 IF ON SKIN (or hair): Remove/Take off immediately contaminated clothing. Brise skin with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P363 Wash contaminated clothing before reuse. P363 Wash contaminated clothing before reuse.	an if n a tion. ly all l r for ghtly

Non-GHS hazard statement

AUH066 'Repeated exposure may cause skin dryness or cracking'.



Other hazards

May form explosive peroxides.

This mixture does not contain substances known as prohibited carcinogen, an illicit drug precursor, or a chemical of security concern.

This mixture does not contain substances that are PBT or vPvB. This mixture does not cause endocrine disruption.

SECTION 3: COMPOSITION AND INFORMATION ON INGREDIENTS

Mixture

Chemical name	CAS No.	%W/W	Classification in accordance with GHS 7, (HCIS) and ECHA	Additional information
Ethanol	64-17-5	≥60 - <70	Flammable liquid – cat. 2	-
Molybdenum oxide (MoO₃)	1313-27-5	≥30 - <40	Carcinogenicity cat. 2 Eye irritation – cat.2 Specific target organ toxicity (single exposure) – cat. 3	-
Vanadic acid, (HVO₃), ammonium salt	7803-55-6	≥2 - <7	Acute toxicity (oral) – cat. 3 Eye irritation – cat. 2 Acute toxicity (inh.) – cat. 4 Toxic to reproduction – category 2 (oral) (developmental toxicity) Specific target organ toxicity - (repeated exposure) (respiratory track) (inhalation) – cat. 1 Aquatic toxicity – chronic – cat. 2	-
Mica-group minerals	12001-26-2	<7	Not classified	-
Ethanol, 2-butoxy-	111-76-2	≥0.5 - <2	Acute toxicity (inh.) – cat. 3 Acute toxicity (oral) – cat. 4 Eye irritation – cat. 2 Skin irritation – cat. 2	Inhalation: ATE = 3 mg/L (Vapours) Oral: ATE = 1200 mg/kg bw
Acetic acid, ethyl ester	141-78-6	≥0.5 - <2	Flammable liquid – cat. 2 Specific target organ toxicity (single exposure) – cat. 3 Eye irritation – cat. 2	AUH066 (Repeated exposure may cause skin dryness and cracking)
Solvent naphtha (petroleum), light, aromatic	64742-95-6	≥0.3 - <1	Aspiration hazard – cat. 1 Carcinogenicity – cat. 1B Germ cell mutagenicity – cat. 1B	-
Fatty acids, C18- unsatd., dimers, reaction products with N,N-dimethyl- 1,3-propanediamine and 1,3- propanediamine	162627-17-0	≥0.3 - <1	Sensitisation – skin Cat. 1A	-
Methanol	67-56-1	<0.3	Flammable liquid – cat. 2 Acute toxicity (oral) – cat. 3 Acute toxicity (dermal) – cat. 3 Acute toxicity (ing.) – cat.3	-



	Specific target organ toxicity	
	(single exposure) – cat. 1	

SECTION 4: FIRST AID MEASURES

Description of necessary first aid m	easures
General notes	If symptoms occur, consult a doctor. Show this safety data sheet to the doctor in attendance.
Following inhalation	May cause respiratory irritation. Remove person to fresh air and keep comfortable for breathing. If symptoms occur: Get medical advice/attention.
Following skin contact (or hair contact)	Highly flammable liquid and vapour. May cause an allergic skin reaction. Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation or rash occurs: Get medical advice/attention.
Following eye contact	Causes serious eye irritation. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Following ingestion	Harmful if swallowed. Call a POISON CENTER or doctor/ physician if you feel unwell.
Self-protection of the first aider	Ensure that you are wearing the appropriate personal protective equipment according to the incident, injury, and surroundings.

Symptoms caused by exposure

Highly flammable liquid and vapour. Harmful if swallowed. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child (oral) (developmental toxicity). May cause damage to organs through prolonged or repeated exposure (respiratory tract, inhalation).

Medical attention and special treatment

Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

Suitable extinguishing equipment

Suitable Extinguishing media	Foam, water spray, carbon dioxide or dry powder. Use water to
	cool fire-exposed containers and to disperse vapour.
Unsuitable extinguishing media	Do not use water jet. Direct water jet may spread the fire.



Specific hazards arising from the chemical

Highly flammable liquid and vapour. May form explosive peroxides. Cool containers exposed to flames with plenty of water until well after the fire is out. Vapour may form explosive mixture with air. Vapour is heavier than air and may accumulate in confined spaces.

This material is harmful to aquatic life with long lasting effects. Fire water contaminated with the material must be contained; do not empty into drains. Run off to sewer may cause fire or explosion hazard.

Special protective equipment and precautions for firefighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Move containers from the fire area if it is safe to do so. Cool containers exposed to flames with plenty of water until well after the fire is out. Do not allow product or run-off to enter drains, sewers, or watercourses.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

For non-emergency responders	Eliminate sources of ignition. Ensure adequate ventilation. Do not touch or walk through split material. Avoid contact with skin, eyes, or clothing. Do not breathe fumes/ mist/ vapours/ spray. Wear suitable personal protective equipment, (see Section 8). The vapour is heavier than air; it will concentrate in low lying areas; beware of pits and confined spaces.
For emergency responders	Keep unnecessary personnel away. Wear suitable personal protective equipment, including gloves, goggles/face shield, boots, and protective clothing. Wear appropriate respirator when ventilation is inadequate (see section 8). Do not breathe fumes/mist/vapours/spray. Ensure adequate ventilation. Avoid contact with skin, eyes, or clothing. The vapour is heavier than air; it will concentrate in low lying areas, beware of pits and confined spaces.

Environmental precautions

The product is harmful to aquatic life with long lasting effects. Collect spillage. Do not allow to enter drains, sewers, or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the appropriate regulatory body.

Methods and material for containment and cleaning up

For containmentStop the leak if it is safe to do so. Contain the spillage with sand, earth, or
any suitable non-combustible adsorbent material.For cleaning upUse sand, earth, or any suitable non-combustible adsorbent material to
adsorb spillages. Using non-sparking tools transfer the contaminated
absorbent material into a UN approved container for disposal. Containers
should be sealed before being disposed of via an authorised waste disposal
contractor.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. explosion-proof [electrical/ventilating/lighting/] equipment. Use non-sparking tools. Take action to prevent static discharges.



Do not breathe fumes/ mist/ vapours/ spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/eye protection/face protection/ hearing protection.

Do not eat, drink, or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Ground and bond container and receiving equipment. Keep only in original container and keep it tightly closed. Store in a well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. Keep away from direct sunlight.

Storage temperature	Ambient
Storage life	12 months
Incompatible materials	Keep away from strong acids and oxidising agents. Do not store in aluminium metal

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure control measures

Hazardous Chemical Information System (HCIS)

Ingredient	CAS No.	Long-term exposure limit (8-hr TWA reference period)		Short-term exposure limit (15-min reference period)		Note
		ppm	mg/m³	ppm	mg/m³	
Ethanol	64-17-5	1000	1880	-	-	-
Molybdenum, soluble compounds (as Mo)		-	5	-	-	
Molybdenum, insoluble compounds (as Mo)	-	-	10	-	-	-
Mica (inspirable)	12001-26-2	-	2.5	-	-	-
2-butoxyethanol	111-76-2	20	96.9	50	242	Sk.
Ethyl acetate	141-78-6	200	720	400	1440	-
Solvent naphtha (petroleum), light, aromatic	64742-95-6	500	-	-	-	UK (1)
Methanol	67-56-1	200	262	250	328	Sk.

Sk.: Can be absorbed through the skin.

(1) Value for aromatics, approved by ACTS. Hydrocarbon solvents supplied as a complex mixture, HSE ACTS procedure, see EH40, paragraphs 84-87.

Biological monitoring

Source UK EH40/2005, 4th edition 2020.

Ingredient	Biological monitoring guidance value	Sampling time
2-butoxyethanol	240 mmol butoxyacetic acid/mol creatinine in urine	Post shift

Control Banding

Not available



Engineering controls

Provide adequate ventilation, including appropriate local extraction, to minimise exposure to vapours. A washing facility/water for eye and skin cleaning purposes should be present.

Individual protection measures, for example personal protective equipment (PPE)

Eye and face protection



Skin protection - hand



Skin protetion - other

Respiratory protection



Thermal hazards

General hygiene

Wear safety glasses with side protection (EN166).

Wear chemical resistant gloves (EN 374). Contact glove supplier to confirm suitable glove material, thickness, and breakthrough times. If contact with forearms is likely, wear gauntlet-style gloves.

Wear long sleeve chemical resistant protective clothing. Plastic apron. Nitrile rubber boots.

In the case of insufficient ventilation, wear respiratory equipment. Suitable respiratory protection for lower concentrations or short-term effect: Filter type ABEK-P3 (EN 14387).

None known.

Do not eat, drink, or smoke when using this product. t. Take off immediately all contaminated clothing. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Paste, yellow colour.
Odour	Characteristic
Odour threshold	Not available
рН	No data available
Melting point/freezing point	No data available
Boiling point and boiling range	No data available
Flash point	14 °C (calculated)
Evaporation rate	Not available
Flammability (solid, gas)	Not applicable
Upper/lower flammability or explosive limits	UEL: 19% (w/w); LEL: 1.1% (w/w)
Vapour pressure	No data available
Vapour density	No data available
Relative density	No data available
Solubility	Soluble in water
Partition coefficient: n-octanol/water	No data available for the mixture
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Viscosity	No data available
Specific heat value	No data available



No data available

GMS Marking Fluid 12-04-2024 Version 1

Saturated vapour concentration Release of invisible flammable vapours and gases Particle size Size distribution Redox potential Biodurability or biopersistence

No data available No data available Not applicable May form explosive peroxidesI Low potential for bioaccumulation. Some ingredients are readily biodegradable

SECTION 10: STABILITY AND REACTIVITY

Reactivity

Stable under recommended storage conditions.

Chemical stability

Stable under normal conditions.

Possibility of hazardous reactions

Highly flammable liquid and vapour. May form explosive peroxides. Vapour may form explosive mixture with air. Vapour is heavier than air and may accumulate in confined spaces.

Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Keep away from direct sunlight.

Incompatible materials

Keep away from strong acids and oxidising agents. Keep away from metals and aluminium.

Hazardous decomposition products

Carbon oxides (CO and CO₂), nitrogen oxides (NO and NO₂), molybdenum oxides and vanadium oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on hazard classes as defined in GHS Version 7

Acute toxicity	
Acute toxicity - Oral	Acute toxicity – oral – Category 4. Harmful if swallowed. Acute toxicity estimate (ATE): 300 – 2000 mg/kg bw
Acute toxicity - Dermal	Not classified. Based on the available data, the classification criteria are not met.
Acute toxicity - Inhalation	Not classified. Based on the available data, the classification criteria are not met. Acute toxicity estimate (ATE): > 20 mg/L.

Ingredient	Acute toxicity - oral	Acute toxicity - dermal	Acute toxicity - inhalation
Ammonium	LD ₅₀ : 141.43 mg/Kg (rat,	LD ₅₀ > 2000 mg/Kg (rats,	LC50: 2.43 mg/L (rats,
trioxovanadate	female)	male and female)	female) (air)
2-butoxyethanol	LD ₅₀ : 1200 mg/Kg (guinea pig, male and female)	LD ₅₀ > 2000 mg/Kg (guinea pig, male and female)	LC ₅₀ : 3 mg/L (vapours)
Methanol	The classification is only based upon the experiences in humans and classifies methanol as acutely toxic by oral, dermal and inhalative exposure		



Skin corrosion/irritation	Not classified. Based on the available data, the classification criteria are not met.
Serious eye damage/irritation	Serious eye damage/irritation – Category 2. Causes serious eye irritation.
Respiratory or skin sensitisation	
Respiratory sensitisation	Not classified. Based on the available data, the classification criteria are not met.
Skin sensitisation	Sensitisation – Skin – Category 1A. May cause an allergic skin reaction.
Germ cell mutagenicity	Germ cell mutagenicity – Category 1B. May cause genetic defects.
Carcinogenicity	Carcinogenicity – Category 1B. May cause cancer.
Reproductive toxicity	Toxic to reproduction – Category 2. Suspected of damaging fertility or the unborn child (oral) (developmental toxicity).
Specific Target Organ Toxicity (STOT) – single exposure	Specific target organ toxicity (single exposure) – Category. May cause respiratory irritation.
Specific Target Organ Toxicity (STOT) –	Specific target organ toxicity (repeated exposure) – Category 2. May
repeated exposure	cause damage to organs through prolonged or repeated exposure (respiratory tract, inhalation).
Aspiration hazard	Not classified. Based on the available data, the classification criteria are not met.

Information on possible routes of exposure

Ingestion	Harmful if swallowed
Skin contact	May cause an allergic skin reaction. Repeated exposure may cause skin dryness or
	cracking.
Eye contact	Causes serious eye irritation
Inhalation	May cause respiratory irritation

Early onset symptoms related to exposure

Harmful if swallowed. Suspected of damaging fertility or the unborn child (oral)
(developmental toxicity).
May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking. May cause genetic defects. May cause cancer.
Causes serious eye irritation.
May cause damage to organs through prolonged or repeated exposure (respiratory tract, inhalation).

Delayed health effects from exposure

None known.

Exposure levels and health effects

Not available.

Interactive effects

None known.

When specific chemical data is not available

The classification of the mixture has been done based on the available information of the components.



Mixtures of chemicals

Ingredient	CAS No.	%W/W	Classification in accordance with GHS 7, (HCIS) and ECHA	Notes
Ethanol	64-17-5	≥60 - <70	Flammable liquid – cat. 2	Not applicable
Molybdenum trioxide	1313-27-5	≥30 - <40	Carcinogenicity cat. 2 Eye irritation – cat.2 Specific target organ toxicity (single exposure) – cat. 3	Sufficient to contribute to the overall health effects of the mixture.
Ammonium trioxovanadate	7803-55-6	≥2 - <7	Acute toxicity (oral) – cat. 3 Eye irritation – cat. 2 Acute toxicity (inh.) – cat. 4 Toxic to reproduction – category 2 (oral) (developmental toxicity) Specific target organ toxicity - (repeated exposure) (respiratory track) (inhalation) – cat. 1 Aquatic toxicity – chronic – cat. 2	Acute toxicity: calculation method. Other classifications: sufficient to contribute to the overall health effects of the mixture.
Mica	12001-26-2	<7	Not classified	Not applicable
2-butoxyethanol	111-76-2	≥0.5 - <2	Acute toxicity (inh.) – cat. 3 Acute toxicity (oral) – cat. 4 Eye irritation – cat. 2 Skin irritation – cat. 2	Acute toxicity: calculation method. Other classifications: not sufficient to contribute to the overall health effects of the mixture.
Ethyl acetate	141-78-6	≥0.5 - <2	Flammable liquid – cat. 2 Specific target organ toxicity (single exposure) – cat. 3 Eye irritation – cat. 2	Not sufficient to contribute to the overall health effects of the mixture.
Solvent naphtha (petroleum), light, aromatic	64742-95-6	≥0.3 - <1	Aspiration hazard – cat. 1 Carcinogenicity – cat. 1B Germ cell mutagenicity – cat. 1B	Aspiration hazard: Not sufficient to contribute to the overall health effects of the mixture. Other classifications: Sufficient to contribute to the overall health effects of the mixture.
Condensation products of dimerised fatty acids, C18- unsaturated, with N,N-dimethyl-1,3- propanediamine and 1,3-propanediamine	162627-17-0	≥0.3 - <1	Sensitisation – skin Cat. 1A	Sufficient to contribute to the overall health effects of the mixture.
Methanol	67-56-1	<0.3	Flammable liquid – cat. 2 Acute toxicity (oral) – cat. 3 Acute toxicity (dermal) – cat. 3 Acute toxicity (ing.) – cat.3 Specific target organ toxicity (single exposure) – cat. 1	Acute toxicity: calculation method. Other classifications: not sufficient to contribute to the overall health effects of the mixture.

Other information

The mixture does not contain any ingredient that is known to cause endocrine disruption.



SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Aquatic Chronic 3. Harmful to aquatic life with long lasting effects.

Data on aquatic toxicity

Ammonium trioxovanadate CAS 7803-55-6

Acute (short-term) toxicity Fish (Leuciscus idus) – fresh water Fish (Limanda limanda) – marine water Invertebrates (Daphnia magna) – fresh water Invertebrates (Americamysis bahia) – marine water Algae (Scenedesmus subspicatus) – fresh water

Chronic (long-term) toxicity Fish (Jordanella floridae) – fresh water Invertebrates (Daphnia magna) – fresh water Algae (Scenedesmus subspicatus) – fresh water LC₅₀ 96-h: 0.693 mg V/L (V₂O₅) LC₅₀ 96-h: 27.800 mg V/L (NH₄VO₃) LC₅₀ 48-h: 1.520 mg V/L (V₂O₅) LC₅₀ 48-h: 13.300 mg V/L (NaVO₃) EC₅₀ 72-h: 2.907 mg V/L (V₂O₅)

EC₁₀ 30-d: 0.076 mg V/L (V₂O₅) NOEC 98-d: 0.560 mg V/L (NaVO₃) EC₁₀ 72-h: 0.716 mg V/L (V₂O₅)

Persistence and degradability

No data available on the mixture. The following data are for the product components:

Ingredient	Data
Ethanol	Readily biodegradable
Molybdenum trioxide	Not relevant for inorganic substances
Ammonium trioxovanadate	Not relevant for inorganic substances
Mica	Not relevant for inorganic substances
2-butoxyethanol	Readily biodegradable
Ethyl acetate	Readily biodegradable
Solvent naphtha (petroleum), light, aromatic	Not relevant for UVCB hydrocarbon
Condensation products of dimerised fatty acids, C18- unsaturated, with N,N-dimethyl-1,3- propanediamine and 1,3-propanediamine	Readily biodegradable
Methanol	Readily biodegradable

Bioaccumulative potential

No data available on the mixture. The following data are for the product components:

Ingredient	Partition coefficient n-octanol /water (Log Kow)	Bioconcentration factor (BCF)
Ethanol	Low potential for bioaccumulation Log Kow (Log Pow): -0.35 at 20 °C	BCF: 1 - 3 at 20 °C
Molybdenum trioxide	Not applicable for inorganic substances	BCF: The lowest bioaccumulation factor observed was 0.05
Ammonium trioxovanadate	Not applicable for inorganic substances	BCF: 12.3 L/kg ww
Mica	Not applicable for inorganic substances	-
2-butoxyethanol	Log Kow (Log Pow): 0.81 at 20 °C	-
Ethyl acetate	Log Kow (Log Pow): 0.68 at 25 °C	BCF: 30 on aquatic species at 22.5 °C



Solvent naphtha (petroleum), light, aromatic	Not relevant for UVCB hydrocarbon	-
Condensation products of dimerised fatty acids, C18- unsaturated, with N,N-dimethyl-1,3- propanediamine and 1,3-propanediamine	Log Kow (Log Pow): > 5.5 at 20 °C	Study technically not feasible
Methanol	Log Kow = - 0.77 at 20 °C	BCF: < 10

Mobility in soil

Ammonium trioxovanadate is readily soluble in water (7.81 g/L). It is expected to be highly mobile in soils.

Inorganic substances and organic solvents (ethanol, 2-butoxyethanol, ethyl acetate) are also readily soluble in water and expected to be mobile in soils.

Condensation products of dimerised fatty acids, C18-unsaturated, with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine (Log Koc: >5.6) and solvent naphtha (petroleum), light aromatic are poorly soluble and expected to persist in soils.

Results of PBT and vPvB assessment

This mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Endocrine disrupting properties

This mixture does not cause endocrine disruption.

Other adverse effects

No known significant effects or critical hazards.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal methods

Product and packaging to be disposed of as hazardous waste. Disposal should be in accordance with local, state, or national legislation. Harmful to aquatic life with long lasting effects. Do not landfill.

Empty containers retain product residue and can be hazardous. Dispose of uncleaned empty containers as hazardous waste in accordance with local, state, or national legislation.

Contaminated adsorbent must be removed in sealed, plastic lined drums and disposed of via an authorised waste disposal contractor. Do not empty into drains; dispose of this material and its container in a safe way.

For the safety of persons conducting disposal, recycling or reclamation activities, reference to the information in section 8 – Exposure Controls and Personal Protection.



SECTION 14: TRANSPORT INFORMATION

According to ADG/IMDG/ICAO/IATA.

UN number

UN 1210

UN Proper Shipping Name or Technical Name PRINTING INK RELATED MATERIAL

Transport hazard class

3

Packing group

ш

Environmental hazards for transport purposes

None

Special precautions for user

None

Additional information

None

Hazchem or Emergency Action Code

3YE

SECTION 15: REGULATORY INFORMATION

Safety, health, and environmental regulations

This SDS has been prepared in accordance with Preparation of safety data sheets for hazardous chemicals Code of Practice 2021.

This product has been classified according to Work Health and Safety Regulations.

Australian Inventory of Chemical Substances (AICS)

Chemical name	CAS No.	Specific Information Requirement
Ethanol, 2-butoxy-	111-76-2	Obligations to provide information apply. You must tell us within 28 days if the circumstances of your importation or manufacture (introduction) are different to those in our assessment.
Fatty acids, C18-unsatd., dimers, reaction products with N,N- dimethyl-1,3-propanediamine and 1,3-propanediamine	162627-17-0	Obligations to provide information apply. You must tell us within 28 days if the circumstances of your importation or manufacture (introduction) are different to those in our assessment.



SECTION 16: OTHER INFORMATION

Date of preparation or review

Version number 1 Date 12/04/2024.

Key abbreviations or acronyms used

ADG Code	The Australian Code for the Transport of Dangerous Goods by Road and Rail
ATE	Acute toxicity estimate
AUH	Australian Hazard Statement
BCF	Bioconcentration factor
CAS number	Chemical Abstracts Service number
ECHA	European Chemicals Agency
GHS 7	Globally Harmonized System of Classification and Labelling of Chemicals 7th revised edition
ΙΑΤΑ	International Air Transport Association
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organisation
L(E)C ₅₀	Lethal concentration, 50%; Effect concentration, 50%
LD ₅₀	Lethal dose, 50%
LEL	Lower explosion limit
NOEC	No observed effect concentration
PBT	Persistent, bioaccumulative and toxic
UEL	Upper explosion limit
UVCB	Unknown or variable composition, complex reaction products or of biological materials
vPvB	very Persistent and very Bioaccumulative

Key literature references and sources for data

Model Work Health and Safety Regulations, 2023 Schedule 10. Prohibited carcinogens, restricted carcinogens, and restricted hazardous chemical, of WHS Regulations Preparation of safety data sheets for hazardous chemicals. Code of Practice, 2021 National Code of Practice for Chemicals of Security Concern Classifying hazardous chemicals. National guide, June 2023 Hazardous Chemical Information System (HCIS) Search Hazardous Chemicals Search Exposure Standards Australian Inventory of Industrial Chemicals (Inventory) ECHA dossiers EH40/2005 4th Edition, 2020 Endocrine Disruptor Lists (https://edlists.org/)

Classification and procedure used to derive the classification for mixtures

Classification according to Work Health and Safety Regulations and GHS 7	Classification procedure
Flammable liquid – Category 2	Flash point
Acute toxicity – oral – Category 4	Calculation
Sensitisation – Skin – Category 1A	Calculation method
Serious eye damage/irritation – Category 2	Calculation method
Specific target organ toxicity (single exposure) – Category 3	Calculation method
Germ cell mutagenicity – Category 1B	Calculation method



SAFETY DATA SHEET

GMS Marking Fluid 12-04-2024 Version 1

Carcinogenicity – Category 1B Toxic to reproduction – Category 2 Specific target organ toxicity (repeated exposure) – Category 2 Aquatic toxicity – chronic – category 3

Calculation method Calculation method Calculation method Summation method

End of safety data sheet

DISCLAIMER

Information contained in this publication or as otherwise supplied to users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Pryor Marking Technology gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Pryor Marking Technology accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.